

# **GTI NB-IoT Chipset Certification Report**

The logo consists of the letters 'GTI' in a bold, white, sans-serif font, centered within a circular blue grid pattern that recedes into a bright light source in the background.

**GTI**

---

# GTI

<b>Version:</b>	V1.0.0
<b>Deliverable Type</b>	<input type="checkbox"/> Procedural Document <input checked="" type="checkbox"/> Working Document
<b>Confidential Level</b>	<input checked="" type="checkbox"/> Open to GTI Operator Members <input type="checkbox"/> Open to GTI Partners <input type="checkbox"/> Open to Public
<b>Working Group</b>	Terminal WG
<b>Task</b>	PM3-PJ5: IoT Program / Device Certification Project
<b>Source members</b>	
<b>Support members</b>	
<b>Editor</b>	GTI Certification Office
<b>Last Edit Date</b>	2018-XX-XX
<b>Approval Date</b>	

# 1 Overview

The certification Report specifies a synthetic assessment for NB-IoT product. The assessment includes conformance, network compatibility, Tx/Rx power, RF accuracy and power consumption. The document is for industrial reference.

## 2 Product Information

GENERAL INFORMATION		
1	Product Manufacturer	
2	Product TYPE(CHIPSET/MODULE/DEVICE)	
3	Product identifier (Model Name or Number)	
4	Hardware Version	
5	Software Version	
6	Primary Function Description (NB-IoT/eMTC)	
7	Certified Band	

## 3 Certification Result

The test results of DUT in protocol & RF conformance, network compatibility, TX/RX performance and power consumption demonstrate that the product is GTI certified.

### 3.1 Protocol Conformance Test

Table 3-1 Protocol Conformance Test Result

Item	Available cases	Executed cases	Test Results
Category "M"			
Category "O"			

### 3.2 RF Conformance Test

Table 3-2 Protocol Conformance Test Result

Item	Available cases	Executed cases	Test Results
Category "M"			
Category "O"			

### 3.3 RRM Conformance Test

Table 3-3 RRM Conformance Test Result

Item	Available cases	Executed cases	Test Results
Category "M"			
Category "O"			

### 3.4 Network Compatibility Test

#### 3.4.1 Operating Mode

Table 3-4 Operating Mode

	Huawei	ZTE	Ericsson	Nokia	DATANG
Stand-alone					
In-Band					
Guard Band					

#### 3.4.2 Uplink and Downlink Subcarrier Spacing

Table 3-5 Uplink and Downlink Subcarrier Spacing

	Huawei	ZTE	Ericsson	Nokia	DATANG
UL 3.75kHz ST					
UL 15kHz ST					
UL 15kHz MT					
DL 15kHz					

#### 3.4.3 Paging

Table 3-6 Paging

	Huawei	ZTE	Ericsson	Nokia	DATANG
Paging					

#### 3.4.4 Short Message Service

Table3-7 SMS

	Huawei	ZTE	Ericsson	Nokia	DATANG
Short Message Service(SMS)					

### 3.4.5 Data Transmission

Table 3-8 Data Transmission

	Huawei	ZTE	Ericsson	Nokia	DATANG
Control Plane					
User Plane					

### 3.4.6 Transfer Protocol

Table 3-9 Transfer Protocol

	Huawei	ZTE	Ericsson	Nokia	DATANG
IP					
NoN-IP					

### 3.4.7 Power Saving Function

Table 3-10 Power Saving Function

	Huawei	ZTE	Ericsson	Nokia	DATANG
PSM					
eDRX					

### 3.4.8 Mobility Function

Table 3-11 Mobility Function

	Huawei	ZTE	Ericsson	Nokia	DATANG
Cell Reselection					

### 3.4.9 Rate Performance ( R13 )

Table 3-12 Peak Rate(Unit: kbps)

	MCL≤144dB		MCL=154dB		MCL=164dB	
	UL	DL	UL	DL	UL	DL
Huawei						
ZTE						
Ericsson						
Nokia						
DATANG						

### 3.5 RF Performance Test

Note: Category "C" Test Cases. Up to manufacture to decide whether release test results in this Part

#### 3.5.1 Maximum Transmitting Power

Table 3-13 Maximum Transmitting Power Test Result

No	Cell Parameter NRS EPRE (dBm/15KHz)	Test Result (dBm)
1	-88	
2	-112	
3	-132	

#### 3.5.2 RX Sensitivity

The DUT **meets** the RX Sensitivity requirement ( $MCL \geq 164\text{dB}$ ) in Standalone/Guardband mode.

Note: the Rx sensitivity requirements for category-NB UE is  $-121\text{dBm}/200\text{kHz}$  in standalone/Guardband mode and  $-129\text{dBm}/200\text{kHz}$  in In-band mode.

#### 3.5.3 Measurement Accuracy Test

##### (1). Test Results in Ideal Environment

Table 3-14 NRSRP accuracy in Ideal Environment

Expected RF Measurement Value	Accuracy Biases
-88dBm	
-112dBm	

-132dBm	
---------	--

## (2). RF Measurement Accuracy Test in AWGN Environment

Table 3-15 NRSRP accuracy in AWGN environment

Expected Value \ SNR	Accuracy Biases			
	20dB	10dB	0dB	-5dB
-88dBm				
-112dBm				
-132dBm				

Table 3-16 SNR accuracy in AWGN environment

Expected Value \ NRS EPRE	Accuracy Biases			
	20dB	10dB	0dB	-5dB
-88dBm				
-112dBm	NA			

## (3) RF Measurement Accuracy Test in Interference Environment

Table 3-17 NRSRP accuracy in Interference environment

Expected Value \ SNR	Accuracy Biases			
	20dB	10dB	0dB	-5dB
-88dBm				
-112dBm				
-132dBm	NA	NA	-0.8	

## 3.6 Power Consumption Test

*Note: Category "C" Test Cases. Up to manufacture to decide whether release test results in this Part*

Table 3-18 Certification Results of Power Consumption

Status	Result
PSM	
IDLE (Paging Cycle=2.56s)	
eDRX cycle (20.48s)	

eDRX cycle (81.92s)		
eDRX cycle (655.36s)		
Average Current during Registration		
Duration of Registration		
Data transfer	0dB TX Power	
	Max TX Power	
Data receive		

## 4 Document Change Record

Date	Version	Change History
XXXX-XX-XX	1.0.0	Initial Version

The last page

---